

07 > CONTATORI LANCIA IMPULSI THREADED WATER METERS

THREADED WATER METERS



A-CON
A-CON



DESCRIZIONE/DESCRIPTION

Contatori lancia impulsu filettati.
Threated Water Meters with pulse output.




CARATTERISTICHE TECNICHE/TECHNICAL FEATURES

Calibro - Size - DN Gauge - Size - DN	mm	13	20	25	30	40	50
Portata massima Qmax (CEE) Qmax max. flow rate (CEE)	m ³ /h	3	5	7	10	20	30
Portata nominale QN (CEE) QN Nominal flow rate (CEE)	m ³ /h	1.5	2.5	3.5	5	10	15
Portata Minima Qmin (CEE) Minimum Flow Qmin (CEE)	l/h	30	50	70	100	200	450
Massima temperatura dell'acqua Minimum Working Temperature	°C	40	40	40	40	40	40
Massima pressione di lavoro Max Working Pressure	BAR	16	16	16	16	16	16
Emettitore impulsu Pulse emitter	4 imp/lt (k=0.25)						



DIMENSIONI/DIMENSIONS



Codice Code	Modello Model	Connessioni Connections	D	DN	Qn	PN	L	I	Price (€)
		Ø mm	mm	mm	m ³		mm	mm	
ADCONRC00	A-CON/C 1/2"	1/2"	3/4"	13	1.5	16	110	190	
ADCONRC01	A-CON/C 3/4"	3/4"	1"	20	2.5	16	130	230	
ADCONRC02	A-CON/C 1"	1"	1" 1/4	25	3.5	16	260	360	
ADCONRC03	A-CON/C 1 1/4"	1" 1/4	1" 1/2	30	5	16	260	380	
ADCONRC04	A-CON/C 1 1/2"	1" 1/2	2"	40	10	16	300	440	
ADCONRC05	A-CON/C 2"	2"	2" 1/2	50	15	16	300	460	

Codice Code	Modello Model	Connettore Connector	Ingresso-Uscita In-Out	Impulsi Pulses	Portata nom. Flow-rate nom.	Price (€)
					m ³ /h	
ADCONRC00	Connettore filettato Threated water meter	HIRSMANN	G 1/2"	4 IMP/lt	1,5	
ADCONRC000B	Connettore filettato Threated water meter	BNC	G 1/2"	4 IMP/lt	1,5	
ADCONRC01	Connettore filettato Threated water meter	HIRSMANN	G 3/4"	4 IMP/lt	2,5	
ADCONRC010B	Connettore filettato Threated water meter	BNC	G 3/4"	4 IMP/lt	2,5	
ADCONRC02	Connettore filettato Threated water meter	HIRSMANN	G 1"	4 IMP/lt	3,5	
ADCONRC020B	Connettore filettato Threated water meter	BNC	G 1"	4 IMP/lt	3,5	
ADCONRC03	Connettore filettato Threated water meter	HIRSMANN	G 1" 1/4	4 IMP/lt	5	
ADCONRC030B	Connettore filettato Threated water meter	BNC	G 1" 1/4	4 IMP/lt	5	
ADCONRC04	Connettore filettato Threated water meter	HIRSMANN	G 1" 1/2	4 IMP/lt	10	
ADCONRC040B	Connettore filettato Threated water meter	BNC	G 1" 1/2	4 IMP/lt	10	
ADCONRC05	Connettore filettato Threated water meter	HIRSMANN	G 2"	4 IMP/lt	15	
ADCONRC050B	Connettore filettato Threated water meter	BNC	G 2"	4 IMP/lt	15	