

## POOL LINING PVC SKIMMER



Kit rivestimento in PVC per tecnologia a skimmer calcolato per parete h120 h220 e parete h140 fondo piano

*PVC LINING KIT FOR SKIMMER TECHNOLOGY suitable for h 120 h 220 wall and h 140 wall, flat bottom*



### CAMPO DI UTILIZZO

Piscine pubbliche e private per rivestimento in membrane di PVC  
Tecnologia a Skimmer con rivestimento in membrane di PVC



### CONTEXT OF USE

*Public and private pools with PVC membrane lining  
Skimmer technology with PVC membrane lining*



### DESCRIZIONE

Profilo in PVC 25x20x3 in aste da 3 mt  
Rotoli Elbe H 1.65 in rotoli da L 25 MT - L 12,5 mt  
Profilo in PVC flexiflow interno  
Profilo in PVC flexiflow esterno  
Rivetti in alluminio 3,4x11 in conf.100 pz  
Chiodi ad espansione  
PVC liquido per sigillatura chimica del PVC del colore del rivestimento  
Solvente THF per saldatura  
Applicatore per PVC liquido



### DESCRIPTION

*PVC profile 25x20x3 in 3 m bars.  
Elbe rolls H 1.65 L 25 m - L 12.5 m  
Internal Flexiflow PVC profile  
External Flexiflow PVC profile  
Aluminium rivets 3.4x11 - package 100 pcs  
Expansion bolts  
Liquid PVC for chemical sealing of PVC lining colour  
THF thinner for welding  
Liquid PVC applicator*



### CARATTERISTICHE TECNICHE

Fabbricato in PVC, completamente riciclabile. Proprietà chimiche e meccaniche che vengono assicurate dagli additivi rispettosi delle leggi internazionali. Il PVC non rilascia diossine nell'atmosfera e può essere riciclato mediante degassificazione, il PVC è normalmente riutilizzato per ulteriori pavimentazioni. Resistente e impermeabile, costruito con PVC rinforzato con uno spessore di 1,50 mm assicura una perfetta tenuta della piscina. Liscio e piacevole al tatto, è durevole nel tempo e facile da mantenere. Stabile contro i raggi UV. Resistente al maltempo e al freddo. Antimicrobi. Saldabile. Privo di metalli pesanti e fisicamente testato secondo EN 71/3. Resistente ai prodotti per la pulizia della vasca e ai detergenti per la depurazione dell'acqua se effettuata attenendosi perfettamente alle indicazioni e con una temperatura dell'acqua fino a 28°C.



### TECHNICAL FEATURES

*Made in fully recyclable PVC. Chemical and mechanical properties are ensured by additives in compliance with international regulations. PVC does not release dioxins into the atmosphere and can be recycled through degasification. After recycling, it is normally reused to produce materials for floor lining. Strong and waterproof, made in reinforced PVC with a thickness of 1.50 mm, it guarantees excellent pool sealing. Smooth and pleasant to the touch, durable and low-maintenance. UV-resistant. Resistant to adverse weather conditions and cold temperatures. Antimicrobial. Weldable. Free from heavy metals and physically tested in compliance with EN 71/3. Resistant to pool detergents and water purification products, if these are used according to the instructions and with a water temperature up to 28°C.*



### OPTIONAL

Codice/Code	Descrizione/Description	Price (€)
800800072	Collante per rivestimento Kg 5/ Kg 5 glue for pool lining	
808800033	Materassino h 1500 L 15 mt sp.5 mm a cellula chiusa per pareti e fondo/Closed-cell technology mat h 1500 L 15 m thickness 5 mm for walls and floor	
808800034	Materassino H 1500 L 15 mt sp.10 mm a cellula chiusa per pareti e fondo/Closed-cell technology mat H 1500 L 15 m thickness 10 mm for walls and floor	

# 08 > KIT-rivestimento KIT-pool lining

Dimensione (m) Dimension (m)	Rotoli h 1,65 mt. 25 Rolls h 1.65 m 25	Rotoli h 1,65 antiscivolo m <sup>2</sup> Non-slip h 1.65 rolls sq. m	PVC liquido Kg 1 Liquid PVC kg 1	Profilo pvc per ancoraggio mt. 50 PVC profile for fastening m 50	Profilo in alluminio mt.3 Aluminium profile m 3	Profilo in alluminio mt.3 pretagliato Pre-cut aluminium profile m 3	Chiodi ad espansione 4.8x26 Expansion bolts 4.8x26	Rivetti 3.4x11 conf. 50 Rivets 3.4x11 - package 50 pcs	RIVESTIMENTO ELBTAL colori (azzurro-blu-bianco-grigio-grigio scuro- sabbia) ELBTAL LINING colours (light blue-blue-white-grey-dark grey-sand)
---------------------------------	---	---	-------------------------------------	---	--	--	---	---	--

## RETTANGOLARE/RECTANGULAR

3.20x7.20	1½		1	50	21			50	Cod. KEK100
4.00x8.00	2		1	50	24			100	Cod. KEK101
4.00x8.00+R1.5	2½	8.25	1	50	21	6	5	100	Cod. KEK102
4.00x8.00+RET 1.6x2.4	2½	8.25	1	50	30		5	100	Cod. KEK103
4.80x9.60	2½		1	50	30			100	Cod. KEK104
4.80x9.60+R1.5	3	8.25	1	50	27	6	5	100	Cod. KEK105
4.80x9.60+RET 1.6x2.4	3	8.25	1	50	33		5	100	Cod. KEK106
5.00x10.00	3		1	50	30			100	Cod. KEK107
5.00x10.00+R1.5	3½	8.25	2	50	27	6	5	150	Cod. KEK108
5.00x10.00+RET 1.6x2.4	3½	8.25	2	50	36		5	150	Cod. KEK109
5.60x11.20	3½		2	50	36			150	Cod. KEK110
5.60x11.20+R1.5	4	8.25	2	50	33	6	5	150	Cod. KEK111
5.60x11.20+RET 1.6x2.4	4	8.25	2	50	39		5	150	Cod. KEK112
6.00x12.00	4		2	50	36			150	Cod. KEK113
6.00x12.00+R1.5	4	8.25	2	50	33	6	5	150	Cod. KEK114
6.00x12.00+RET 1.6x2.4	4	8.25	2	50	42		5	150	Cod. KEK115
6.80x12.80	4½		2	50	42			150	Cod. KEK116
6.80x12.80+R 1.5	5	8.25	2	50	39	6	5	200	Cod. KEK117
6.80x12.80+RET 1.6x2.4	5	8.25	2	50	45		5	200	Cod. KEK118
7.00x14.00	5		2	50	42			200	Cod. KEK119

## ORIONE

4.00x8.00	2		1	50	18	9		150	Cod. KEK120
5.00x10.00	2½		1	50	21	9		150	Cod. KEK121
6.00x12.00	3½		2	50	24	12		150	Cod. KEK122

## SIRIO

4.00x8.00	2		1	50	9	15		150	Cod. KEK123
5.00x10.00	2½		1	50	9	18		150	Cod. KEK124
6.00x12.00	3		2	50	9	21		200	Cod. KEK125

## ANDROMEDA

4.00x8.00	2		1	50		21		150	Cod. KEK126
5.00x10.00	2½		1	50		27		150	Cod. KEK127
6.00x12.00	3½		1	50		33		200	Cod. KEK128

Aggiungere le prime due lettere del colore di rivestimento scelto al codice del kit (per es. Sa-Sabbia, Bi-bianco, ecc. ) per identificare il prodotto.  
Add the first two letters of the lining color to the code of the chosen kit (for example Sa-Sand, Wh-White, ecc. ) to identify the product.